

Rev/0625

Technical parameters for heat pump space heaters and heat pump combination heaters

Model(s):				IPHP 014 R290			
Air-to-water heat pump:				yes			
Water-to-water heat pump:				no			
Brine-to-water heat pump:				no			
Low-temperature heat pump:				yes			
Equipped with a supplementary heater:				no			
Heat pump combination heater:				yes			
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.							
Parameters shall be declared for average, colder and warmer climate conditions.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	38	kW	Seasonal space heating energy efficiency	η sh	170.20	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = − 7 °C	Pdh	33.1	kW	T j = − 7 °C	COPd or PERd	2.89	– or %
T j = + 2 °C	Pdh	20.1	kW	T j = + 2 °C	COPd or PERd	4.15	– or %
T j = + 7 °C	Pdh	15.0	kW	T j = + 7 °C	COPd or PERd	5.84	– or %
T j = + 12 °C	Pdh	16.3	kW	T j = + 12 °C	COPd or PERd	7.43	– or %
T j = bivalent temperature	Pdh	33.1	kW	T j = bivalent temperature	COPd or PERd	2.89	– or %
T j = operation limit temperature	Pdh	30.4	kW	T j = operation limit temperature	COPd or PERd	2.63	– or %
For air-to-water heat pumps: T j = − 15 °C (if TOL < − 20 °C)	Pdh	0.0	kW	For air-to-water heat pumps: T j = − 15 °C (if TOL < − 20 °C)	COPd or PERd	0.00	– or %
Bivalent temperature	T biv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcyc	0.0	kW	Cycling interval efficiency	COPcyc or PERcyc	0.00	– or %
Degradation co-efficient (**)	Cdh	0.9	—	Heating water operating limit temperature	WTOL	0	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P OFF	0.00	kW	Rated heat output (*)	Psup	0.0	kW
Thermostat-off mode	P TO	0.30	kW	Type of energy input	Electricity		
Standby mode	P SB	0.11	kW				
Crankcase heater mode	P CK	0.00	kW				
Other items				For air-to-water heat pumps: Rated air flow rate, outdoors			
Capacity control	Variable			—	20524	m ³ /h	
Sound power level, indoors/ outdoors	LWA	83	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	QHE	18030	kWh	—	0	m ³ /h	
Declared load profile	Average			Water heating energy efficiency	η wh	-	%
Daily electricity consumption	Q elec	-	kWh	Daily fuel consumption	Q fuel	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	Gj
Contact details	TRANE 88190 Golbey - France						
Item							